

Uncontrolled document as of December 19, 2012. Refer to website for up to date specifications.

CASES
1430
Top Loader Case




1430 Top Loader Case

- Unique top loading design
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dust proof

1430 Top Loader Case Configurations

Cat. #	Description
1430	1430 Top Loader Case
1434	1430 Case with Padded Dividers & Lid Organizer
1437	1430 Case with Padded Office Divider Set & Lid Organizer
1430NF	1430 Top Loader Case (No foam)



1430 Top Loader Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
16.93" x 9.61" x 13.42" (43 x 24.4 x 34.1 cm)		13.56" x 5.76" x 11.70" (34.4 x 14.6 x 29.7 cm)	
Lid Depth	Bottom Depth	Total Depth	
2.00" (5.1 cm)	9.70" (24.6 cm)	11.70" (29.7 cm)	

Interior Cubic Volume
0.53 cubic feet (14.98 cubic decimeter)

Weight with foam	Weight without foam	Buoyancy Max.
6.5 lbs. (2.95 kg)	5.6 lbs. (2.54 kg)	59 lbs. (26.76 kg)

Range Temperature
-40 / 210° F (-40 / 99° C)

Personalized Nameplate Available

1430 Top Loader Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1430 Top Loader Case Accessories

Cat. #	Description
1430PF	Special Application Panel Frame
1431	5 pc. Replacement Foam Set
1432	Strap Kit
1433	Replacement O-ring
1435	Padded Divider Set Only
1436	Office Divider Kit
1438	Boat Bracket Kit
1439	Lid Organizer

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com