

Uncontrolled document as of November 20, 2012. Refer to website for up to date specifications.

CASES 1550 Case



1550 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

1550 Case Configurations

Cat. #	Description
1550	1550 Case
1554	1550 Case with Padded Dividers
1550NF	1550 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1550 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
20.62" x 16.87" x 8.12" (52.4 x 42.8 x 20.6 cm)	18.43" x 14.00" x 7.62" (46.8 x 35.5 x 19.3 cm)	
Lid Depth	Bottom Depth	Total Depth
1.75" (4.4 cm)	5.87" (14.9 cm)	7.62" (19.3 cm)

Interior Cubic Volume

1.14 cubic feet (32.22 cubic decimeter)

Weight with foam	Weight without foam	Buoyancy Max.
11.9 lbs. (5.4 kg)	10.58 lbs. (4.8 kg)	69.89 lbs. (31.7 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Personalized Nameplate Available

1550 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 8 1-41/STANAG 4280 • ATA 300

1550 Case Accessories

Cat. #	Description
1550PF	Special Application Panel Frame
1551	4 pc. Replacement Foam Set
1552	Pick N Pluck™ Sections Only (set of 2)
1553	Replacement O-ring
1555	Padded Divider Set Only

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com