

CASES
1660
Case



1660 Case

- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Large 2-person fold down handles
- Stainless steel hardware and padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dust proof

1660 Case Configurations

Cat. #	Description
1660	1660 Case
1664	1660 Case with Padded Dividers
1660NF	1660 Case (No foam)



Black



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1660 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
31.59" x 22.99" x 19.48" (80.2 x 58.4 x 49.5 cm)		28.20" x 19.66" x 17.63" (71.6 x 49.9 x 44.8 cm)	
<i>This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.</i>			
Lid Depth	Bottom Depth	Total Depth	
3.50" (8.9 cm)	14.14" (35.9 cm)	17.64" (44.8 cm)	
Interior Cubic Volume			
5.66 cubic feet (160.17 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
42.16 lbs. (19.12 kg)	34.16 lbs. (15.49 kg)	350.1 lbs. (158.8 kg)	
Range Temperature	No. of Wheels	Retractable Handle	

Personalized Nameplate Available

1660 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1660 Case Accessories

Cat. #	Description
1661	5 pc. Replacement Foam Set
1662	Pick N Pluck™ Sections Only (set of 3)
1663	Replacement O-ring
1665	Padded Divider Set Only
1669	Photo/Lid Organizer for 1660 Case

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com