

CASES
iM2075
 Pelican Storm Case



iM2075 Pelican Storm Case

- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2075 Pelican Storm Case Configurations

Cat. #	Description
iM2075-X0001	iM2075 Pelican Storm Case
iM2075-X0000	iM2075 Storm Case (No foam)
iM2075-X0002	iM2075 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2075 Pelican Storm Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
11.80" x 9.80" x 7.70" (30 x 24.9 x 19.6 cm)		9.50" x 7.50" x 7.25" (24.1 x 19 x 18.4 cm)	
Lid Depth	Bottom Depth	Total Depth	
1.50" (3.8 cm)	5.75" (14.6 cm)	7.25" (18.4 cm)	
Interior Cubic Volume			
0.3 cubic feet (8.46 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
3.7 lbs. (1.68 kg)	3.3 lbs. (1.5 kg)	28.45 lbs. (12.9 kg)	
Range Temperature			
-20 / 140° F (-29 / 60° C)			

iM2075 Pelican Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2075 Pelican Storm Case Accessories

Cat. #	Description	Sug. Retail
iM-LIDSTAY	Lid Stay	US\$30.87
iM-STRAP-S-VER2	Padded Shoulder Strap	US\$25.75
iM-VALVE-M-B	Manual Purge Valve	US\$7.16
iM2075-DIV	Padded Dividers	US\$58.95
iM2075-FOAM	4 pc. Replacement Foam Set	US\$28.95
iM20XX-BEZEL	Base Bezel Kit	US\$48.95

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
 e-mail: CSR.Consumer@pelican.com • www.pelican.com