

CASES
iM2500
 Pelican Storm Case



iM2500 Pelican Storm Case (Carry On Case)

- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2500 Pelican Storm Case (Carry On Case) Configurations

Cat. #	Description
iM2500-X0001	iM2500 Pelican Storm Case (Carry On Case)
iM2500-X0000	iM2500 Storm Case (No foam)
iM2500-X0002	iM2500 Storm Case with Padded Dividers



iM2500 Pelican Storm Case (Carry On Case) Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
21.70" x 14.10" x 8.90" (55.1 x 35.8 x 22.6 cm)		20.50" x 11.50" x 7.20" (52 x 29.2 x 18.3 cm)	
Lid Depth	Bottom Depth	Total Depth	
2.00" (5.1 cm)	5.20" (13.2 cm)	7.20" (18.3 cm)	
Interior Cubic Volume			
0.98 cubic feet (27.82 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
13.7 lbs. (6.21 kg)	11.1 lbs. (5.03 kg)	62.56 lbs. (28.38 kg)	
Range Temperature	No. of Wheels	Retractable Handle	
-20 / 140° F (-29 / 60° C)	2	YES	

iM2500 Pelican Storm Case (Carry On Case) Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2500 Pelican Storm Case (Carry On Case) NSN List

Part Number	NSN #	Description
IM2500-30000	8145-01-540-4449	Storm Case iM2500, OD, Empty
IM2500-00001	8145-01-540-4447	Storm Case iM2500, Black, Cubed Foam
IM2500-00000	8145-01-540-4461	Storm Case iM2500, Black, Empty

iM2500 Pelican Storm Case (Carry On Case) Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-STRAP-S-VER2	Padded Shoulder Strap
iM-VALVE-M-B	Manual Purge Valve
iM2500-BEZEL	Base Bezel Kit
iM2500-BEZEL-LID	Lid Bezel Kit
iM2500-DIV	Padded Dividers
iM2500-FOAM	5 pc. Replacement Foam Set
iM2500-UTILITYORG	Utility Organizer

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com