



iM3410 Pelican Storm Case

- Waterproof, Crushproof and Impact Protected
- Pressure Relief Valve
- Tough Hinges
- In-line Wheels
- Five Press & Pull Latches
- Four Reinforced Padlockable Hasps
- Lightweight Strong HPX® Resin
- Guaranteed For Life

iM3410 Pelican Storm Case Configurations

Cat. #	Description
iM3410-X0001	iM3410 Pelican Storm Case
iM3410-X0000	iM3410 Storm Case (No foam)



Black



OD Green

iM3410 Pelican Storm Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
57.74" x 12.71" x 6.67" (146.6 x 32.3 x 16.9 cm)	54.50" x 10.00" x 6.00" (138.4 x 25.4 x 15.2 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	4.00" (10.2 cm)	6.00" (15.2 cm)
Interior Cubic Volume		
1.89 cubic feet (53.59 cubic decimeter)		
Weight with foam	Weight without foam	Buoyancy Max.
20 lbs. (9.07 kg)	18 lbs. (8.16 kg)	

Range Temperature	No. of Wheels
-20 / 140° F (-29 / 60° C)	2

iM3410 Pelican Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM3410 Pelican Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM3410-FOAM	4 pc. Replacement Foam Set

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com