



1555

Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 40 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- Super-light proprietary HPX²™ Polymer
- Business card holder
- Learn more about Pelican Air



CONFIGURATIONS



1555
Standard



1555NF
No Foam



1555WD
With Padded Dividers



1555TP
With TrekPak Divider System



1555WF
With Foam

DIMENSIONS

Interior (L x W x D)	23.00 x 12.75" x 7.50 (58.4 x 32.4 x 19.1 cm)
Exterior (L x W x D)	24.76 x 15.46" x 8.24 (62.9 x 39.3 x 20.9 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.50" (14 cm)
Total Depth	7.5" (19.1 cm)
Int Volume	1.27 ft ³ (0.036 m ³)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Yellow	 Silver	 Orange
---	--	--	--

WEIGHT

Weight With Foam	9.02 lbs (4.1 kg)
Weight Empty	7.37 lbs (3.3 kg)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Buoyancy

81.20 lbs (36.8 kg) sales@pelican.com • www.pelican.com

TEMPERATURE

Document created on 02-12-19

Minimum Temperature -60°F (-51.1 °C)

Maximum Temperature 160°F (71.1 °C)

FOAM PROPERTIES

Layer 1 (Lid) 2.03" Convolute

Layer 2 (Base) 2.25" Pick N Pluck

Layer 3 (Base) 2.25" Pick N Pluck

Layer 4 (Base) 0.90" Pad

ACCESSORIES
